







**Notes:**








1. F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
3. It is recommended that add an ESD protection chip to the JTAG download circuit.



**Notes:**

1. F CLK signal is an external input clock signal. It is recommended that F CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs. For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
3. It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
A3	GW2A-LV18MG196	2.0
Date:	Friday, March 31, 2023	Sheet 2 of 13

**Notes:**

- F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
- External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
- It is recommended that add an ESD protection chip to the JTAG download circuit.

Title	
GOWIN Minimum System Diagram	
Size	Rev
A3	2.0
Date: Friday, March 31, 2023	Sheet 3 of 13

D

C

B

A

D


C

B

A












Title	
GOWIN Minimum System Diagram	
Size A3	Document Number GW2A-LV18PG256C
Rev 2.0	
Date: Friday, March 31, 2023	Sheet 4 of 13


**Notes:**

1. F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
3. It is recommended that add an ESD protection chip to the JTAG download circuit.

Title	
GOWIN Minimum System Diagram	
Size A3	Document Number GW2A-LV18PG256CF
Date: Friday, March 31, 2023	Rev 2.0
Sheet 5	of 13





- Notes:**
1. F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
 2. External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
 3. It is recommended that add an ESD protection chip to the JTAG download circuit.

**Notes:**

1. F_CLK signal is an external input clock signal. It is recommended that F_CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs. For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
3. It is recommended that add an ESD protection chip to the JTAG download circuit.


Title	
GOWIN Minimum System Diagram	
Size A3	Document Number GW2A-LV18PG256S
Date: Friday, March 31, 2023	Rev 2.0



**Notes:**

- F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
- External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
- It is recommended that add an ESD protection chip at the JTAG download circuit.

Title		GOWIN Minimum System Diagram	
Size	Document Number	Rev	2.0
C	GW2A-LV18PG484	Date	Friday, March 31, 2023
Sheet	9	of	13



Notes:



1. F_CLK signal is an external input clock signal.

It is recommended that F_{CLK} signal be provided through an active oscillator crystal.






2.External Flash memory is used to store downloaded programs.


For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG234.


3. It is recommended that add an ESD protection chip to the JTAG download circuit.

**Notes:**

1. F CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
3. It is recommended that add an ESD protection chip to the JTAG download circuit.







Notes:

- NOTES**

 - 1.F_{_}CLK signal is an external input clock signal.
It is recommended that F_{_}CLK signal be provided through an active oscillator crystal.
 - 2.External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
 - 3.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
C	GW2A-LV18UG464	2.0
Date:	Friday, March 31, 2023	Sheet 13 of 13