






GW1N-LV2CS100H




Notes:

- 1.F CLK signal is an external input clock signal. It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size B	Document Number GW1N-LV2CS100H	Rev 2.1
Date: Tuesday, April 09, 2024	Sheet 1	of 33

GW1N-LV2CS42




Notes:

- 1.F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
A4	GW1N-LV2CS42	2.1
Date:	Wednesday, April 10, 2024	Sheet 2 of 33

GW1N-LV2CS42H



- Notes:
- 1.F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
 - 2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title
GOWIN Minimum System Diagram

Size
A4

Document Number
GW1N-LV2CS42H

Rev
2.1

Date: Tuesday, April 09, 2024

Sheet 3 of 33

D

C

B


A

D






C

B



A




Notes:
 1.F CLK signal is an external input clock signal.
 It is recommended that F_CLK signal be provided through an active oscillator crystal.
 2.It is recommended that add an ESD protection chip to the JTAG download circuit.














Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-LV2LQ100	2.1
Date:	Tuesday, April 09, 2024	Sheet 4 of 33

1













- Notes:
- 1.F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
 - 2.It is recommended that add an ESD protection chip to the JTAG download circuit.






Notes:
 1.F_CLK signal is an external input clock signal.
 It is recommended that F_CLK signal be provided through an active oscillator crystal.
 2.It is recommended that add an ESD protection chip to the JTAG download circuit.




Notes:
1.F_CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-LV2MG121	2.1
Date:	Tuesday, April 09, 2024	Sheet 9 of 33

**Notes:**

- 1.F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.


Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-LV2MG121X	2.1
Date:	Tuesday, April 09, 2024	Sheet 10 of 33



Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.








Title			
GOWIN Minimum System Diagram			
Size B	Document Number GW1N-LV2MG132		Rev 2.
Date:	Tuesday, April 09, 2024	Sheet	11 of 33



Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-LV2MG132H	2.1
Date: Tuesday, April 09, 2024		
Sheet 12 of 33		






Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-LV2MG132X	2.1
Date:	Tuesday, April 09, 2024	Sheet 13 of 33

GW1N-LV2MG49





Notes:

1.F_CLK signal is an external input clock signal.





It is recommended that F_CLK signal be provided through an active oscillator crystal.

2.It is recommended that add an ESD protection chip to the JTAG download circuit.





Notes:

- NOTES:
- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
 - 2.It is recommended that add an ESD protection chip to the JTAG download circuit.







Title				
GOWIN Minimum System Diagram				
Size B	Document Number GW1N-LV2QN32			Rev 2.
Date:	Tuesday, April 09, 2024	Sheet	15 of 33	

GW1N-LV2QN32X









Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection circuit to the JTAG download circuit.



Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-LV2QN32X	2.1
Date:	Tuesday, April 09, 2024	Sheet 16 of 33









Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-LV2QN48	2.1
Date:	Tuesday, April 09, 2024	Sheet 17 of 33


GW1N-LV2QN48H



Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.







Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-LV2QN48H	2.1
Date:	Wednesday, April 10, 2024	Sheet 18 of 33



Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.







Title			
GOWIN Minimum System Diagram			
Size B	Document Number GW1N-LV2QN88		Rev 2.
Date:	Tuesday, April 09, 2024	Sheet 19 of 33	









Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.


Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-UV2LQ100	2.1
Date:	Tuesday, April 09, 2024	Sheet 20 of 33










Notes:


- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.



Notes:






- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.








Notes:








- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.















Notes:

- 1.F_CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.












Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-UV2MG121	2.1
Date:	Tuesday, April 09, 2024	Sheet 25 of 33



Notes:
1.F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-UV2MG121X	2.1
Date:	Tuesday, April 09, 2024	Sheet 26 of 33










Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-UV2MG132X	2.1
Date:	Tuesday, April 09, 2024	Sheet 28 of 33

GW1N-UV2MG49





Notes:

1.F_CLK signal is an external input clock signal.





It is recommended that F_CLK signal be provided through an active oscillator crystal.

2.It is recommended that add an ESD protection chip to the JTAG download circuit.





Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection circuit to the JTAG download circuit.







Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-UV2QN32	2.1
Date:	Tuesday, April 09, 2024	Sheet 30 of 33

GW1N-UV2QN32X





Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.







Title			
GOWIN Minimum System Diagram			
Size	Document Number	Rev	
B	GW1N-UV2QN32X	2.1	
Date:	Tuesday, April 09, 2024	Sheet	31 of 33








Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.



Title			
GOWIN Minimum System Diagram			
Size	Document Number	Rev	
B	GW1N-UV2QN48	2.1	
Date:	Tuesday, April 09, 2024	Sheet	32 of 33



Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.It is recommended that add an ESD protection chip to the JTAG download circuit.

Title			
GOWIN Minimum System Diagram			
Size B	Document Number GW1N-UV2QN88	Rev 2.	
Date:	Tuesday, April 09, 2024	Sheet 33 of 33	